

# VersaFLO

**Description & Application:** VersaFLO is a seamless, non-porous flooring choice designed to reduce fatigue. It offers both safety and comfort with minimal upkeep needed. Made with a significant amount of recycled materials, VersaFLO is an eco-friendly flooring option. Whether for a running track, sport court, or specialized training facility, its durable wear layer can be easily recoated, ensuring long-lasting use. Available in a variety of colors, thicknesses, and densities, VersaFLO can be tailored to fit your preferences perfectly.

**Warranty:** Pliteq Flooring warrants that VersaFLO, when installed according to its recommended procedures and adhesives, will be free from manufacturing defects during regular use for 10 years from the original installation date. For more information, please reach out.

## PHYSICAL SPECIFICATIONS

FORMAT **PAD & POUR**  
 DIMENSIONS FLUID APPLIED SEAMLESS SURFACE  
 THICKNESS CUSTOMIZABLE

## TECHNICAL SPECIFICATIONS

	ASTM	
Surface Hardness		81
Shock Absorption (Standard BaseMat)	EN1408	28.3%
7mm BaseMat	EN1408	32%
9mm BaseMat		
Coefficient of Friction		0.56 (Dry) 0.28 (Wet)
Ball Bounce	EN1235	98%
Impact Resistance	EN1235	>800 GR@10C
Resistance to Indentation	EN1516	0.32mm @ 5min
Resistance to Rolling Loads	EN1569	>1500N
Static Load Limit		225 PSI
Tensile Strength	DIN53455	3071 PSI (21N/mm)
Elongation at Break	DIN53455	200%
Tear Strength	DIN53515	294 PLI (52N/mm)

## COLOR OPTIONS

