

# VersaDUEL

**Description & Application:** A durable pre-bonded multi-layer rubber floor system made from recycled rubber and EPDM granules, designed for impact cushioning and injury prevention in fitness centers and high-traffic areas. It provides shock absorption, vibration damping, and noise control for various environments. **VersaDUEL** is used to cushion impacts from falling objects, reduce fatigue, prevent injuries from repetitive motion and standing for long periods, and ease muscle and joint stress.

## PHYSICAL SPECIFICATIONS

| FORMAT       | ROLLS                       |
|--------------|-----------------------------|
| DIMENSIONS   | 4' x 15' (1.2 m x 4.6 m)    |
| THICKNESS    | 9/16" (15mm)                |
| SF/UNIT      | 60 SF (5.6 m <sup>2</sup> ) |
| WEIGHT/ROLL  | 135lb (61.2 kg)             |
| ROLLS/PALLET | 9                           |

| FORMAT      | LARGE SQUARE EDGE TILE                              |
|-------------|-----------------------------------------------------|
| DIMENSIONS  | 24" x 48" (610 mm x 1220 mm),                       |
| THICKNESS   | 9/16" (15mm), 13/16" (20mm), 1" (25mm)              |
| SF/UNIT     | 8 SF (0.75 m <sup>2</sup> )                         |
| WEIGHT/TILE | 19 lbs (8.6 kg), 24 lbs (10.9 kg), 30 lbs (13.6 kg) |
| TILE/PALLET | 40                                                  |

| FORMAT      | SQUARE EDGE TILE                                  |
|-------------|---------------------------------------------------|
| DIMENSIONS  | 24" x 24" (610 mm x 610 mm),                      |
| THICKNESS   | 9/16" (15mm), 13/16" (20mm), 1" (25mm)            |
| SF/UNIT     | 4 SF (0.38 m <sup>2</sup> )                       |
| WEIGHT/TILE | 10 lbs (4.5 kg), 12 lbs (5.5 kg), 15 lbs (6.8 kg) |
| TILE/PALLET | 80                                                |

## TECHNICAL SPECIFICATIONS

|                          | ASTM     | 9/16" - 1" (15mm - 25mm) |
|--------------------------|----------|--------------------------|
| SHORE HARDNESS           | D2240    | >70 (± 5)                |
| COMPRESSION SET          | D395     | -15 to -45% @25%         |
| TABER ABRASION           | C501     | 0.45                     |
| ABRASION RESISTANCE      | D3389    | 0.11g, 300 cycles        |
| WEAR INDEX               | D3389    | 0.386                    |
| TENSILE STRENGTH         | D412     | >300 psi                 |
| ELONGATION AT BREAK      | D412     | >90%                     |
| COEFFICIENT OF FRICTION  | D1894-95 | Wet 1.20 / Dry 1.20      |
| DENSITY                  | D792     | >65 lb/ft <sup>3</sup>   |
| CRITICAL RADIANT FLUX    | D395     | Class I/II               |
| TEAR                     | D624     | 88.07 lbf/in             |
| CHEMICAL RESISTANCE      | F925-02  | No Change                |
| IGNITION CHARACTERISTICS | D2859    | Pass                     |

**Warranty:** Pliteq warrants that VersaDUEL, when installed according to its recommended procedures and adhesives, will be free from manufacturing defects. For more information, please review the Limited Lifetime Warranty document or contact your local Pliteq representative.



1-888-491-6549




info@pliteqflooring.com




www.pliteqflooring.com

# VersaDUEL

## STANDARD COLOR OPTIONS




1710 GAMETIME GREEN




1711 WILDCARD WHITE




1712 STERLING SILVER




1713 BREAKAWAY BLUE



1714 REBOUND RED



1715 OVERTIME ORANGE



1716 COACH CORK




1717 BOLD BLACK


## PREMIUM COLOR OPTIONS



1701 MULCH



1702 SANDSTONE



1703 OBSIDIAN



1704 GRANITE



1705 MARBLE

Additional Colors available, MOQ may apply.



1-888-491-6549



info@pliteqflooring.com



www.pliteqflooring.com