

VersaFLO

Description & Application: VersaFLO is a seamless, non-porous flooring choice designed to reduce fatigue. It offers both safety and comfort with minimal upkeep needed. Made with a significant amount of recycled materials, VersaFLO is an eco-friendly flooring option. Whether for a running track, multisport, or specialized training facility, its durable wear layer can be easily recoated, ensuring long-lasting use. Available in a variety of colors, thicknesses, and densities, VersaFLO can be tailored to fit your preferences perfectly.

TECHNICAL SPECIFICATIONS

PARAMETER	TEST	RESULT	PARAMETER	TEST	RESULT
Surface Hardness		81	Tensile Strength	DIN53455	3071 PSI (21N/mm)
Shock Absorption			Elongation at Break	DIN53455	200%
(Standard BaseMat)	EN1408	28.3%	Tear Strength	DIN53515	294 PLI (52N/mm)
7mm BaseMat	EN1408	32%			
9mm BaseMat					
Coefficient of Friction		0.56 (Dry)			
		0.28 (Wet)			
Ball Bounce	EN1235	98%			
Impact Resistance	EN1235	>800 GR@10C			
Resistance to Indentation	EN1516	0.32mm @ 5min			
Resistance to Rolling Loads	EN1569	>1500N			
Static Load Limit		225 PSI			

PHYSICAL SPECIFICATIONS

FORMAT	PAD & POUR
DIMENSIONS	FLUID APPLIED SEAMLESS SURFACE
THICKNESS	CUSTOMIZABLE

COLOR OPTIONS

			
0725 DUSTY GREY	0720 PASTEL BLUE	0721 GRASS GREEN	0724 LIGHT GREY
			
0713 BEIGE	0717 OXIDE RED	0726 SAPPHIRE BLUE	0727 PALE BROWN

Warranty: Pliteq warrants that VersFLO, when installed according to its recommended procedures and adhesives, will be free from manufacturing defects. For more information, please review the Limited Lifetime Warranty document or contact your local Pliteq representative.